

Thank you for purchasing the **awave** brand series,
They have all passed comprehensive tests to ensure its
consistency and reliability.

FEATURES:

3 Inch Mid-range Speakers
Rated Power : 30W
Glass fiber composite cone
4 Ohm 25.5mm Voice coil
Qms : 3.78
Qes : 1.13
Qts : 0.87
Vas : 1.61 Ltr

PRECAUTIONS:

- Before installing the mounting hole, please confirm that the installation space is appropriate.
- To prevent noise interference, make sure that the wiring is away from the engine, high voltage conductors and other potential sources of noise.
- To prevent short circuits, make sure that the wiring avoids moving parts and sharp edges.
- Before installing this product, please make sure that you have read this installation guide carefully.

AW 30II TECHNICAL PARAMETERS:

Specifications	Mid-range
Power (W)	30
Fo (Hz)	100
Nominal Impedance(Ω)	4
Sensitivity@ 1W/1M (dB)	85
Frequency Range	100Hz~15KHz
Magnet	High-strength Magnetic NdFeB
Voice Coil	25.5mm
Cone	Glass fiber composite cone
Mounting Depth (mm)	41
Mounting Diameter (mm)	78



AW 30II

套装汽车喇叭说明书

COMPONENT SPEAKER USER'S GUIDE

感谢您购买 **awave** 品牌系列中音喇叭，本产品已经通过全面的测试以确保其性能的一致和可靠性。

特性：

3寸中音喇叭

额定功率：30M

玻纤复合音盆

4欧姆 25.5mm音圈

Qms: 3.78

Qes: 1.13

Qts: 0.87

Vas: 1.61Ltr

注意事项：

- 在打安装孔之前，请确认安装空间是否合适。
- 为了防止噪音干扰，请确保接线远离发动机，高压导线和其他潜在的噪音来源。
- 为防止短路，请确保布线避开运动的部件和锋利的边缘。
- 在安装本产品之前，请确保您已经仔细阅读本安装指导。

AW 30II 技术参数：

产品规格	中音
功率 (W)	30
最低谐振频率 (Hz)	100
阻抗 (Ω)	4
灵敏度 (dB)	85
频率范围	100Hz~15KHz
磁 钢	高强磁钕铁硼
音 圈	25.5mm
音 盆	玻纤复合音盆
安装深度 (mm)	41
安装直径 (mm)	78



- 感谢您的阅读
- Thanks for your review